



Dimensions L 11.81 W 0.59 H 0.15

Advantages

- Field replaceable boards for sustainability
- Available in any continuous length to accommodate exacting installations
- Multiple wattages and lumen output for maximum flexibility within any application
- Four (4) standard color temperatures from 2700K-4000K; non-standard available
- Compatible with all common dimmer and control standards such as 0-10V, 3-wire, forward-phase w/neutral, ELV, DALI and DMX
- High efficiency design delivers more lumens per watt
- CV2 is used throughout all Whitegoods Cove Products for color and performance consistency
- 5-year warranty

Technical Data

- form linear
- circuitry parallel
- power (W) 3W, 6W, 10W
- supply type CV
- operating voltage (VDC) 24
- color rendering index Ra min * 82
- viewing angle (°) 110
- LED (SMD) quantity 42
- PCB substrate FR4
- lifetime–L70 (h)** 60,000
- working temperature -20°C - 60°C

*Higher CRI available on some models

**Tested to LM80

Code	Model Name	Power (w)	CCT (k)	Lum.Flux (lm)	lm/watt
610-20204	CV2-A-3W26G	3	2700	456	152
610-20205	CV2-A-3W29G	3	3000	485	162
610-20206	CV2-A-3W36G	3	3500	531	177
610-20207	CV2-A-3W41G	3	4000	540	180
610-20210	CV2-A-6W26G	6	2700	799	133
610-20211	CV2-A-6W29G	6	3000	858	143
610-20212	CV2-A-6W36G	6	3500	935	156
610-20213	CV2-A-6W41G	6	4000	973	162
610-20216	CV2-A-1W26G	10	2700	1274	127
610-20217	CV2-A-1W29G	10	3000	1350	135
610-20218	CV2-A-1W36G	10	3500	1471	147
610-20219	CV2-A-1W41G	10	4000	1520	152