



General: Arcada was designed to perfectly illuminate window frames, arches, doorways and sculptures. Its sharp blade of light creates a perfectly radial distribution, meant to emphasize architectural elements, making them visible from far away.

Fixture Body: Open-pore Anodized and Powder Coated Die-Cast Aluminum.

Glass: Clear UV Resistant Polycarbonate.

Mounting details: The included back plate allows the fixture to be surface mounted directly onto J-boxes (provided by others).

Dimensions/Weight: 6.4" (1.43 lbs)

Driver: Remote, Constant Current 120-277V Dimmable 0-10V.

Wattages: 4.5W & 8W (6.4")

Cable: Fixture comes with 3.28' of power cable.

Safety features: Fixture is equipped with Electrostatic discharge protection (4 KV), Surge Protection (3.75 KV) and Acquastop (anti-wicking).

IP rating: IP65 for protection against dust and water jets from any angle.

IK rating: IK 08

ETL Certification: ETL, wet location

Optics: Fixed with Blade distribution (Radial).

Color temperatures: 2700K – 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



6.4" (4.5W / 8W)


Delivered Lumens*	6.4" [5 CC]	6.4" [8 CC]
RA	424	678

*Values shown for 3000K

Ordering Information							
ARC		BL	64			RA	
Product	Trim/Film	Type	Diameter	Wattage/Operation	Color Temp	Optic	+ Driver (Required) ¹
ARC = Arcada	WH = White BL = Black GR = Gray	BL = Blade	64 = 6.4"	5 CC = 4.5W / Constant Current (350mA) 8 CC = 8W / Constant Current (630mA)	27 = 2700K 30 = 3000K 40 = 4000K	RA = Radial	ECO30W-XXX SOLO50W-XXX SOLO100W-XXX

¹ See page 2

6.4" 4.5W CC



DRIVER OPTIONS (pick one)


C.C. Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtures

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtures

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtures

6.4" 8WW CC



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-4 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-8 fixtures