



<b>RUB-WH-3D-...-CV-GE...</b>			
Delivered Lumens - Narrow Spot			
		<b>Length [Wattage]</b>	
		39 [2.9 CV]	197 [2.9 CV]
CCT	27-	455	2275
	30-	506	2528
	40-	542	2710
<b>Polar Plot / Cone Of Light Multiplier</b>			
		39 [2.9 CV]	197 [2.9 CV]
		1.00	5.00



Beam Angle (0-180) = 114.2  
Beam Angle (90-270) = 133.4

<b>CONE OF LIGHT - 9.8W/reel 3000K</b>		
<b>General Illumination</b>		
<b>RUB-WH-3D-39-2.9-CV-30-GE*</b>		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Width [Ft]**
20	0	61.8
18	0	55.6
16	1	49.5
14	1	43.3
12	1	37.1
10	2	30.9
8	2	24.7
6	4	18.5
4	10	12.4
2	39	6.2

<b>RUB-CON-3D-...-CV-GE...</b>			
Delivered Lumens - Flood			
		<b>Length [Wattage]</b>	
		39 [2.9 CV]	197 [2.9 CV]
CCT	30-	250	1188
<b>Polar Plot / Cone Of Light Multiplier</b>			
		39 [2.9 CV]	197 [2.9 CV]
		-	-



Beam Angle (0-180) = 105.8  
Beam Angle (90-270) = 130.2

<b>CONE OF LIGHT - 9.8W/reel 3000K</b>		
<b>General Illumination</b>		
<b>RUB-CON-3D-39-2.9-CV-30-GE*</b>		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Width [Ft]**
20	0	52.9
18	0	47.6
16	0	42.3
14	0	37.0
12	1	31.7
10	1	26.4
8	1	21.2
6	2	15.9
4	5	10.6
2	21	5.3

\*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.