



Luminaire

- IP66 rated small adjustable and lockable eyeball luminaire. Exterior rated recessed rotational spot light. Finishes almost flush with the mount surface.
- Recessed mounted.
- Precision machined from 70 - 90% recycled aluminum.
- 4, 6 and 9mm beam spreads with multiple optics.
- 95+ CRI with multiple CCTs and optics available.

Mounting¹

- RM = Recessed Mounted with Spring Clip for drywall
- RR = Recessed Mounted with Retaining Ring for mounting in thin material 0.1" (2mm)

Power²

- 2 = 2W (181lm initial at 700mA, 2.9Vf)

CCT (95+ CRI)³

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Optic

- VN = Very Narrow (10°)
- N = Narrow (13°)
- M = Medium (21°)
- F = Flood (31°)
- WF = Wide Flood (71°)
- E = Elliptical (11° x 45°)

Finish

- CA = Clear Anodized
- W = Pure White, RAL9010
- BA = Black Anodized
- CF = Custom finish, specify RAL

Options⁴

- SNT = Snoot
- TMP = Trumpet

Remote Driver⁵

- ECO30W-500 = 0-10V EldoLED ECOdrive 30W for 1-10 fixtures
- SOLO50W-500 = 0-10V EldoLED SOLOdrive 50W for 1-20 fixtures
- SOLO100W-500 = 0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

1. See page 3 for details.
2. Wattage shown is for LED only, system wattage varies depending on driver selected.
3. See photometric data sheet for delivered lumens.
4. See page 4 for details.
5. See driver information for details.

Ordering Information							
Model	Mounting ¹	Power ²	CRI/CCT ³	Optic	Finish	Options ⁴	Driver ⁵
MS-IRIS	RM RR	2	927 930 935 940	VN N M F WF E	CA W BA CF	SNT TMP	ECO30W-500 SOLO50W-500 SOLO100W-500

