



### Luminaire

- IP66 rated miniature wall or floor recessed fitting. Suitable for use in areas subject to foot traffic only. Also suitable for recessing into ceiling canopies if specified with wing.
- Recessed mounted.
- Precision machined from 70 - 90% recycled aluminum.
- 95+ CRI with multiple CCTs and optics available.

### Mounting

- RM = Recessed Mounted

### Power<sup>1</sup>

- 2 = 2W (181lm initial at 700mA, 2.9Vf)

### CCT (95+ CRI)<sup>2</sup>

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

### Optic

- VN = Very Narrow (12°)
- N = Narrow (13°)
- M = Medium (21°)
- F = Flood (32°)
- WF = Wide Flood (63°)
- E = Elliptical (10° x 46°)

### Finish

- CA = Clear Anodized
- W = Pure White, RAL9010
- BA = Black Anodized
- CF = Custom finish, specify RAL

### Remote Driver<sup>4</sup>

- ECO30W-500 = 0-10V EldoLED ECOdrive 30W for 1-10 fixtures
- SOLO50W-500 = 0-10V EldoLED SOLOdrive 50W for 1-20 fixtures
- SOLO100W-500 = 0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

1. Wattage shown is for LED only, system wattage varies depending on driver selected.  
 2. See photometric data sheet for delivered lumens.  
 3. See driver information for details.

Ordering Information						
Model	Mounting	Power <sup>1</sup>	CRI/CCT <sup>2</sup>	Optic	Finish	Driver <sup>3</sup>
MS-MOL	RM	2	927 930 935 940	VN N M F WF E	CA W BA CF	ECO30W-500 SOLO50W-500 SOLO100W-500

