Tadpole



Photometry

Fitting	Polar diagram	LED	Supply	Power	Delivered output
SL Star LED Very Narrow	117° 15 0 15 30 45 60 75 90 105 120 135 120 135 120 125 120 125 120 125 120 125 120 125 120 125 120 125 125 125 125 125 125 125 125 125 125	95 CRI, 3000K	Constant Current 700mA	2W	134lm
SL Star LED Narrow	13.1° 15 0 15 30 45 60 75 90 105 120 120 120 120 135 150	95 CRI, 3000K	Constant Current 700mA	2W	133lm
SL Star LED Medium	20.9° 45 30 15 0 15 30 45 60 75 90 105 120 135 120 135 155 155	95 CRI, 3000K	Constant Current 700mA	2W	130lm
SL Star LED Flood	31.8° 31.8° 31.8° 45 60 75 90 105 120 135 150 155 150 155 150 155	95 CRI, 3000K	Constant Current 700mA	2W	135lm
SL Star LED Wide Flood	62.7° 45 15 0 15 0 15 0 15 15 15 15	95 CRI, 3000K	Constant Current 700mA	2W	152lm
SL Star LED Elliptical	46.1° 10.3° 150 150 165 150 165 150 165 150 165 150 165 165 166 166 167 168 168 168 169 169 169 169 169 169 169 169 169 169	95 CRI, 3000K	Constant Current 700mA	2W	143lm