



Luminaire

- IP66 rated miniature spot light. Adjustable and lockable exterior spot light for accent lighting; very discreet for enhancing architectural details enabling “layers” within landscapes.
- Surface, fixed or spike mounted.
- Precision machined from 70 - 90% recycled aluminum.
- Multiple optics.
- 95+ CRI, multiple CCTs and optics available.

Mounting

- SM = Surface Mounted
- FXD = Fixed¹
- GS = Ground Spike¹

Power²

- 2 = 2W (181lm initial at 700mA, 2.9Vf)

CCT (95+ CRI)³

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Optic

- VN = Very Narrow (12°)
- N = Narrow (13°)
- M = Medium (21°)
- F = Flood (32°)
- WF = Wide Flood (62°)
- E = Elliptical (10° x 46°)

Finish

- BL = Matte Black, RAL9005
- CA = Clear Anodized
- CB = Classic Bronze 34
- CF = Custom finish, specify RAL

Options⁴

- SNT = Snoot
- CWL = Cowl

Remote Driver⁵

- ECO30W-500 = 0-10V EldoLED ECOdrive 30W for 1-10 fixtures
- SOLO50W-500 = 0-10V EldoLED SOLOdrive 50W for 1-20 fixtures
- SOLO100W-500 = 0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

1. See page 3 for details.
2. Wattage shown is for LED only, system wattage varies depending on driver selected.
3. See photometric data sheet for delivered lumens.
4. Snoot and cowl outside same finish as fixture, inside matte black. See page 4 for details.
5. See driver information for details.

Ordering Information							
Model	Mounting	Power ²	CRI/ CCT ³	Optic	Finish	Options ⁴	Driver ⁵
MS-TAD		2					
MS-TAD	SM FXD ¹ GS ¹	2	927 930 935 940	VN N M F WF E	BL CA CB CF	SNT CWL	ECO30W-500 SOLO50W-500 SOLO100W-500

