



**General:** Ture is part of our Crystals collection. A series of small spot lights with crystal diffusers made in different shapes, some clear and some diffused but all of them with the goal to create a unique effect in the space.

**Fixture Body:** Brass (Chromium Plated).

**Diffuser:** Clear Glass.

**Trim:** Trimless.

**Mounting:** Semi-Recessed ceiling.

**Dimensions/Weight:** 0.8" (0.1 lbs) – 1.2" (0.11 lbs) – 1.6" (0.15 lbs)

**Driver:** Remote. Constant Current 120-277V, Dimmable 0-10V.

**Operation:** Constant Current (CC).

**CC features:** Less susceptible to voltage drop (exceeding 32' distance); Allows for dimming down to 0.1%; Fixtures need to be wired in series.

**Wattages:** 1.5W (applicable to all sizes).

**Cable:** Fixture comes with 0.39' of power cable.

**IP rating:** IP52. Protected against vertically falling drops of water.

**ETL Certification:** ETL, damp location

**Optics:** Fixed, General distribution.

**Color temperatures:** 2700K – 3000K – 4000K – 5000K.

**CRI:** 90+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



0.8" (1.5W)



1.2" (1.5W)



1.6" (1.5W)


Delivered Lumens*	0.8"	1.2"	1.6"
GE	143	199	199

\*Values shown for 3000K

Ordering Information							(Required)		
Product	Trim/Film	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing <sup>1</sup>	Drive <sup>1</sup>
TUR = Ture	TL = Trimless	D = Diamond Shaped Crystal	08 = 0.8" 12 = 1.2" 16 = 1.6"	1.5 CC = 1.5W / Constant Current (500mA)	27 = 2700K 30 = 3000K 40 = 4000K 50 = 5000K	GE = General distribution		E84917 (08) E84954 (12) E84901 (16)	ECO30W-500 SOLO50W-500 SOLO100W-500

<sup>1</sup> See page 2

**0.8" 1W CC**



**Housing**

**E84917**  
Recessed Housing




**DRIVER OPTIONS (pick one)**

**C.C. Power supply options (remote only)**

<b>ECO30W-500</b>	<b>SOLO50W-500</b>	<b>SOLO100W-500</b>
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

**1.2" 1W CC**



**Housing**

**E84954**  
Recessed Housing




**DRIVER OPTIONS (pick one)**

**C.C. Power supply options (remote only)**

<b>ECO30W-500</b>	<b>SOLO50W-500</b>	<b>SOLO100W-500</b>
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

**1.6" 1W CC**



**Housing**

**E84901**  
Recessed Housing



**DRIVER OPTIONS (pick one)**

**C.C. Power supply options (remote only)**

<b>ECO30W-500</b>	<b>SOLO50W-500</b>	<b>SOLO100W-500</b>
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures