

Archiline Aluminum Frame



General: Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The PRO version reaches up to 150', making it perfect for tall buildings and towers. Available in Frameless (Drive-Over), Aluminum or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (20 µm), Aluminum finish

Trim: 6060 Anodized Aluminum. Extra clear glass - Tempered

Mounting/Housing: Galvanized Steel (required for in ground installations).

Drive-over: Walk-Over only.

Dimensions/Weight: 14.6" (3.31 lbs) – 22.1" (6.17 lbs) – 41.4" (10.6 lbs) – 60.7" (15.43 lbs)

Driver: Integral 120-277V 1% 0-10V dimming (1% logarithmic dimming curve), or Non-Dim.

Wattages: 14.5W (14.6") – 22W (22.1") – 44W (41.4") – 65W (60.7")

Cable: Fixture comes with 0.66' of cable (Power cable required, ordered separately).

Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.

IK rating: IK 10

ETL Certification: ETL, wet location


Optics: Fixed. Available in Narrow Spot – Spot – Flood – Wide Flood – Elliptic, Asymmetric Wall Washer. Most variants are also available with Dark Light (Anti-glare) system.

Color temperatures: 2700K – 3000K – 3500K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



14.6" (14.5W)

22.1" (22W)

41.4" (44W)

60.7" (65W)

Delivered Lumens (Fixed)*	14.6"	22.1"	41.4"	60.7"
Narrow Spot	1038	1545	2977	–
Spot	1048	1572	3185	–
Flood	974	1557	3067	–
Wide Flood	1085	1630	3363	–
Elliptic/Grazer	1009	1587	3176	–
Wall Washer	1174	1779	3634	–

*Values shown for 3000K

Delivered Lumens (Fixed DarkLight)*	14.6"	22.1"	41.4"	60.7"
Spot	762	363	718	–
Flood	687	288	719	–
Wide Flood	838	282	715	–
Elliptical	792	335	NA	–

*Values shown for 3000K

Ordering Information

AR	RAF				ID					
Product	Mounting/Frame	Type	Length	Wattage	Operation	Color Temp	Optic	+	Housing (Required) ³	Cables ³
AR = Archiline	RAF = Recessed Aluminum Frame	F = Fixed FDL = Fixed DarkLight ¹	15 = 14.6" 22 = 22.1" 41 = 41.4" 61 = 60.7"	15 = 14.5W 22 = 22W 44 = 44W 65 = 65W	ID = Integral (0-10V dim)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	NSP = Narrow Spot ² SP = Spot FL = Flood WFL = Wide Flood EL = Elliptic/Grazer WW = Wall Washer ²		E98671 (15) E98672 (22) E98673 (41) E99760 (61)	E99826 E99822 E99823 E99824 E99825


¹ NA for 61

² NA for FDL

³ See page 2



14.6" 14.5W ID




HOUSING

E98671

Outer Housing



22.1" 22W ID




HOUSING

E98672

Outer Housing



41.4" 44W ID




HOUSING

E98673

Outer Housing



60.7" 65W ID



HOUSING

E99760

Outer Housing



Cables 0-10V

E99826

39.4" power supply cable +0-10V dimming F 5 pin

E99822

196.9" power supply cable +0-10V dimming F 5 pin

E99823

39.4" extension cable for power +0-10V dimming M+F 5 pin

E99824

196.9" extension cable for power +0-10V dimming M+F 5 pin

E99825

393.7" extension cable for power +0-10V dimming M+F 5 pin