



Luminaire

- Designed for the circular economy. Suited to a multitude of applications from museum and gallery, retail, heritage, private residential and commercial.
- Surface mounted.
- Precision machined from 70 - 90% recycled aluminum.
- 95+ CRI with multiple CCTs and optics available.

Mounting

- SM = Surface Mounted

Power¹

- 8 = 8W (798lm initial at 250mA, 34.1Vf)
- 12 = 12W (1513lm initial at 350mA, 36.9Vf)

CCT (95+ CRI)²

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Optic

- VN1 = Very Narrow 1 (14°), 8W Only
- VN2 = Very Narrow 2 (17°), 12W Only
- M = Medium (25°), 12W Only
- F = Flood (34°), 12W Only
- WF = Wide Flood (47°), 12W Only

Finish (interior always matte black)

- W = Pure White, RAL9010
- BL = Matte Black, RAL9005
- CF = Custom finish, specify RAL

Accessories³

- CL = Clear Lens
- DL = Diffused Lens
- HCL = Honeycomb Louver
- SOL = Solite Lens
- SHS = Sharp Spread Lens
- SOS = Soft Spread Lens

Remote Driver⁴

- ECO30W-XXX = 0-10V EldoLED ECOdrive 30W
8W, 250mA, 1 fixture
12W, 350mA, 1 fixture
- SOLO50W-XXX = 0-10V EldoLED
SOLOdrive 50W
8W, 250mA, 1-2 fixtures (1 per output)
12W, 350mA, 1-2 fixtures (1 per output)
- SOLO100W-XXX = 0-10V EldoLED
SOLOdrive 100W
8W, 250mA, 1-4 fixtures (1 per output)
12W, 350mA, 1-4 fixtures (1 per output)

1. Wattage shown is for LED only, system wattage varies depending on driver selected.
2. See photometric data sheet for delivered lumens.
3. Holds up to two accessories. See page 4 for details.
4. See driver information for details.

Ordering Information							
Model	Mounting	Power ¹	CRI/ CCT ²	Optic	Finish	Accessories ³	Driver ⁴
MS-ZTA50B	SM	8	927	VN1	W	CL	ECO30W-XXX SOLO50W-XXX SOLO100W-XXX
		12	930	VN2 M F WF	BL	DL	
			935		HCL	SOL	
			940		SHS	SOS	

