



### Luminaire

- Designed for the circular economy. Suited to a multitude of applications from museum and gallery, retail, heritage, private residential and commercial.
- Surface mounted.
- Precision machined from 70 - 90% recycled aluminum.
- 95+ CRI with multiple CCTs and optics available.

### Mounting

- SM = Surface Mounted

### Power<sup>1</sup>

- 8 = 8W (798lm initial at 250mA, 34.1Vf)
- 12 = 12W (1513lm initial at 350mA, 36.9Vf)

### CCT (95+ CRI)<sup>2</sup>

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

### Optic

- VN1 = Very Narrow 1 (14°), 8W Only
- VN2 = Very Narrow 2 (17°), 12W Only
- M = Medium (25°), 12W Only
- F = Flood (34°), 12W Only
- WF = Wide Flood (47°), 12W Only

### Finish (interior always matte black)

- W = Pure White, RAL9010
- BL = Matte Black, RAL9005
- CF = Custom finish, specify RAL

### Accessories<sup>3</sup>

- CL = Clear Lens
- DL = Diffused Lens
- HCL = Honeycomb Louver
- SOL = Solite Lens
- SHS = Sharp Spread Lens
- SOS = Soft Spread Lens

### Remote Driver<sup>4</sup>

- ECO30W-500 = 0-10V EldoLED ECOdrive 30W for 1 fixture
- SOLO50W-500 = 0-10V EldoLED SOLOdrive 50W for 1-2 fixtures (1 per output)
- SOLO100W-500 = 0-10V EldoLED SOLOdrive 100W for 1-4 fixtures (1 per output)

1. Wattage shown is for LED only, system wattage varies depending on driver selected.  
 2. See photometric data sheet for delivered lumens.  
 3. Holds up to two accessories. See page 4 for details.  
 4. See driver information for details.

Ordering Information							
Model	Mounting	Power <sup>1</sup>	CRI/ CCT <sup>2</sup>	Optic	Finish	Accessories <sup>3</sup>	Driver <sup>4</sup>
MS-ZTA50B	SM	8	927	VN1	W	CL	ECO30W-500 SOLO50W-500 SOLO100W-500
		12	930	VN2 M F WF	BL	DL	
			935		HCL	SOL	
			940		SOS	SOS	

