
ZTA.70 Mains Track +Zoom

inter-lux







0.5" (1/2mm) (3.2" (1/5mm) (5.8")

Luminaire

- Interior rated track spot light with zoomable lens or fixed focus.
- Track mounted (Stucchi Onetrack UL 120V 3 Circuits Common Neutral).
- Precision machined from 70 90% recycled aluminum.
- 95+ CRI with multiple CCTs and optics available.
- Fixture includes 0-10V dimming, driver remote.

Mounting¹

 TR = Stucchi Onetrack UL 120V 3 Circuits Common Neutral

Power²

- 8 = 8W (798lm initial at 250mA, 34.1Vf)
- \blacksquare 12 = 12W (1513lm initial at 350mA, 36.9Vf)
- 24 = 24W (2745lm initial at 700mA, 36.7Vf)

CCT (95+ CRI)3

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Optio

- VN = Very Narrow (11°), 8W Only
- \blacksquare Z1 = Zoom 1 (17° 41°), 12W Only
- Z2 = Zoom 2 (23° 39°), 24W Only
- \blacksquare N = Narrow (15°), 12W Only
- M = Medium (25°), 24W Only
- F1 = Flood 1 (32°), 24W Only
- F2 = Flood 2 (46°), 24W Only
- WF = Wide Flood (61°), 24W Only
- WW = Wall Wash (81° x 41°), 24W Only

Finish (fixture and track adapter) (interior always matte black)

- W = Pure White, RAL9010
- BL = Matte Black, RAL9005
- CF = Custom finish, specify RAL

Options4.5

- SCS = Slash Cut Snoot
- SNT = Straight Snoot
- BD = Barn Doors

Accessories4

- CL = Clear Lens
- DL = Diffused Lens
- HCL = Honeycomb Louver
- SOL = Solite Lens
- SHS = Sharp Spread Lens
- SOS = Soft Spread Lens

Controls (Dimming)⁶

- 010 = 0-10V
- DL = DALI
- W = Wireless (Casambi or Xicato)
- MD = Manual on-board dim
- PC = Phase cut
- Order track separately. See Stucchi Onetrack data sheet for details.
- Wattage shown is for LED only, system wattage varies depending on driver selected.
- 3. See photometric data sheet for delivered lumens.
- 4. Holds one option or accessory. See options on page 5 and accessories on page 6 for details.
- 5. Outside same finish as fixture, inside matte black.
- Do not load driver beyond 76.8W. See driver information for details. Additional drivers available. contact factory.

Ordering Information									
	TR								
Model	Mounting ¹	Power ²	CRI/ CCT ³	Optic	Finish	Options ^{4,5}	Accessories ⁴	+	Controls ⁶
MS-ZTA70MT	TR	8	927 930 935 940	VN	W BL CF	SCS SNT BD	CL DL HCL SOL SHS SOS		010
		12		N					DL W MD PC
		24		M F1 F2 WF WW					
MS-ZTA70MTZ (Zoom)		12		Z1					
		24		Z2					





