
ZTA.70 Surface

inter•lux









Ø2.8" (Ø70mm) 3" (Ø76mm)

2" (51mm)

- Interior rated spot light with zoomable lens or fixed focus optics.
- Surface, stem or pole clamp mounted.
- Precision machined from 70 90% recycled aluminum.
- 95+ CRI with multiple CCTs and optics available.

Mounting

- SM = Surface Mounted
- ST = Stem Mounted1
- PC = Pole Clamp (clamp only, contact us for custom pole options)1

- 8 = 8W (798lm initial at 250mA, 34.1Vf)
- 12 = 12W (1513lm initial at 350mA, 36.9Vf)
- 24 = 24W (2745lm initial at 700mA, 36.7Vf)

CCT (95+ CRI)3

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

- VN = Very Narrow (11°), 8W Only
- N = Narrow (15°), 12W Only
- M = Medium (25°), 24W Only F1 = Flood 1 (32), 24W Only
- F2 = Flood 2 (46°), 24W Only
- WF = Wide Flood (61°), 24W Only
- WW = Wall Wash (81° x 41°), 24W Only

Finish (interior always matte black)

- W = Pure White, RAL9010
- BL = Matte Black, RAL9005
- CF = Custom finish, specify RAL

Options^{4,5}

- SCS = Slash Cut Snoot
- SNT = Straight Snoot
- BD = Barn Doors

Accessories4

- CL = Clear Lens
- DL = Diffused Lens
- HCL = Honeycomb Louver
- SOL = Solite Lens
- SHS = Sharp Spread Lens
- SOS = Soft Spread Lens

Remote Driver⁶

- ECO30W-500 = 0-10V EldoLED ECOdrive 30W for 1 fixture
- SOLO50W-500 = 0-10V EldoLED SOLOdrive 50W for 1-2 fixtures (1 per output)
- SOLO100W-500 = 0-10V EldoLED SOLOdrive 100W for 1-4 fixtures (1 per output)
- 1. See page 5 for details.
- Wattage shown is for LED only, system wattage varies depending on driver selected.
- 3. See photometric data sheet for delivered lumens.
- Holds one option or accessory. See options on page 6 and accessories on page 7 for detials.
- 5. Outside same finish as fixture, inside matte black.
- 6. See driver information for details.

Ordering Information									
MS-ZTA70S									
Model	Mounting	Power ²	CRI/ CCT ³	Optic	Finish	Options ^{4.5}	Accessories ⁴	+	Driver ⁶
MS-ZTA70S	SM ST ¹ PC ¹	8	927 930 935 940	VN N		SCS SNT BD	CL DL HCL SOL SHS SOS		EC030W-500 S0L050W-500 S0L0100W-500
		24		M F1 F2 WF WW					





