



General: Beret is a small and shallow in-grade suitable to illuminate outdoor architectural details such as columns or walls. Beret can also be used as a way finder, or to illuminate landscape details.

Fixture Body: Powder Coated White or Gray, Chrome, Nickel or Stainless Steel.

Trim/Diffuser: Semi-Flush. Extra-clear glass.

Mounting/Casing: Black, ABS casings available for both Concrete or Tile installation.

Drive-over: Walk-over only.

Dimension/Weight: 1.4" (0.14 lbs)

Driver: Remote, Constant Current. 120-277V Dimmable 0-10V or Non-Dim.

CC features: Less susceptible to voltage drop (exceeding 32' distance); Allows for dimming down to 0.1%; Fixtures need to be wired in series.

Wattage: 1W & 2W (1.4")

Cable: Fixture comes with 3.28' of power cable and built-in Aquastop® (anti-wicking) system

IP rating: IP66 for protection against dust and powerful water jets from any angle.

IK rating: IK 05

ETL Certification: ETL, wet location

Optics: Fixed, with round or square aperture. Available in Narrow Spot – Spot – Flood – Wide Flood – Lambertian.

Color temperatures: 2700K – 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



1.4" (1W) Round Aperture



1.4" (2W) Round Aperture



1.4" (2W) Square Aperture

Delivered Lumens*	1W	2W
NSP	–	170
SP	85	148
FL	93	135
WFL	91	149
LAM	–	145

*Values shown for 3000K

Ordering Information							(Required) ³		
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing	Driver
BER = Beret	SSFWHR = Square Semi-Flush White Round Aperture ¹ SSFGRR = Square Semi-Flush Gray Round Aperture ¹ SSFCHR = Square Semi-Flush Chrome Round Aperture SSFNIR = Square Semi-Flush Nickel Round Aperture SSFSTR = Square Semi-Flush St. Steel Round Aperture SSFCHS = Square Semi-Flush Chrome Square Aperture SSFNIS = Square Semi-Flush Nickel Square Aperture SSFSTS = Square Semi-Flush St. Steel Square Aperture	F = Fixed	14 = 1.4"	1 CC = 1W / Constant Current (350mA) 2 CC = 2W / Constant Current (630mA)	27 = 2700K 30 = 3000K 40 = 4000K	NSP = Narrow Spot ² SP = Spot FL = Flood WFL = Wide Flood LAM = Lambertian ²	+	E84915 (1W) E84336 (1W) E84918 (2W)	ECO30W-XXX SOLO50W-XXX SOLO100W-XXX


¹ 1W ONLY

² 2W ONLY

³ See page 2




1.4" 1W Round Aperture



Housing

E84915
Recessed Housing



E84336
Recessed Housing



DRIVER OPTIONS (pick one)


C.C. Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtures

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtures

1.4" 2W Round Aperture



Housing

E84918
Recessed Housing



DRIVER OPTIONS (pick one)


C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures

1.4" 2W Square Aperture



Housing

E84918
Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures