



Contents

- 2 product configurator
- 2 diagrams / drivers



2.4" X 9.8" (7.5W)

General: Giotto is a family of compact, low profile LED downlights and pendants that provides a very defined and surprisingly wide beam in only 0.35" of aperture. An innovative solution called "Cross Optics Technology" uses two convex lenses facing each other. With one lens gathering all the light into one point and the other one opening the beam again, but without any secondary at this point, the result is a very defined and powerful lighting solution in the smallest body.

Fixture Body: Powder Coated Aluminum 6026 (superior corrosion resistance)

Trim: Bezel, Round.

Mounting: Suspension.

Dimensions/Weight: 2.4" Diam. X 9.8" H. (0.99 lbs)

Driver: Remote, 120-277V Dimmable 0-10V or Non-Dim.

Operation: Constant Current (CC)

CC features: Less susceptible to voltage drop (exceeding 32' distance); Allows for dimming down to 0.1%; Fixtures need to be wired in series.

Wattage: 7.5W (2.4" X 9.8")

Cable: Fixture comes with 4.92' of power cable.

IP rating: IP20. Fixture is protected against solid objects greater than 0.5". Not suitable for Outdoor applications or any contact with water.

ETL Certification: ETL, dry location

Optics: Fixed (refer to Giotto Recessed spec sheet for Recessed version).

Available in Spot – Flood – Wide Flood.

Color temperatures: 2700K – 3000K – 3500K – 4000K.

CRI: 92

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.


Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Delivered Lumens*	2.4" X 9.8" (7.5W)
SP	61
FL	161
WFL	110

*Values shown for 3000K

Ordering Information							(Required)	
Product	Trim/Finish	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Driver
GIO = Giotto	RWH = Round White RBL = Round Black	P = Pendant	24X10 = 2.4" (Dia.) x 9.8" (H)	8 CC = 7.5W / Constant Current (630mA)	92-27 = 2700K 92-30 = 3000K 92-35 = 3500K 92-40 = 4000K	SP = Spot (14°) FL = Flood (35°) WFL = Wide Flood (54°)		ECO30W-XXX SOLO50W-XXX SOLO100W-XXX

2.4" X 9.8" 7.5W 630mA



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630

0-10V EldoLED
ECOdrive 30W
for 1-3 fixtures

SOLO50W-630

0-10V EldoLED
SOLOdrive 50W
for 1-4 fixtures

SOLO100W-630

0-10V EldoLED
SOLOdrive 100W
for 1-8 fixtures