

Rubber 3D RGBW



General: Rubber is a broad family of flexible lighting fixtures created to resolve even the most challenging architectural details and applications (columns, curved walls), both indoor and outdoor. Rubber is available in multiple solutions: from a 3D version with a diffused output that bends in every direction, to 2D Mini (only 0.2" wide) options that bend sideways, to get to the unique 3D Optic.

3D Optic has dedicated optics every inch which make this 360° bendable product a real lighting machine, unique in its category and with an unprecedented attention to its design and look.

Fixture Body: Polyurethane resin blended into a PVC flexible channel. Rubber 3D RGBW bends 360° (Min. Bending Radius 9.9").

Mounting/Casing: Multiple mounting solutions available: straight PVC or Aluminum channels and mounting clips with or without wireway; articulated channel to follow any shape the product is bent to.

Drive-over: Walk-Over only.

Dimensions/Weight: 39.5" (0.61 lbs) – 197" (3.01 lbs)

Driver: Remote, 24V DC DMX dimmable.

Wattages: 4.6 W/ft. Individual fixture wattage: 15W (39.5") – 75W (197")

Cable: Fixture comes with 0.82' of cable (Power cable required, ordered separately).

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.

IK rating: IK 07

ETL Certification: ETL, wet location


Optics: Fixed, diffused.

Color temperatures: RGBW (White 3000K).

CRI: 90

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



Nominal Lumens RGBW	39.5"	197"
Red	96	480
Green	316	1580
Blue	71	355
White 3K	361	1805

Ordering Information							(Required) ¹			
Product	Trim/Finish	Type	Length	Wattage/Operation	Color Temp	Optic	+	Profile	Cable	Driver
RUB = Rubber	WH = White Finish	3D = 3D	39 = 39.5" 197 = 197"	5 CVDMX = 4.6W/ft / Remote Constant Voltage 24V DC	R3 = RGBW 3K	GE = General Illumination		E99549 E-K100007 E83034 E-K100009 E-F400001 E-F400002 E-F400003 E-F400004 E-K100011 E99539 E99521	E-W200005 E-W200006	EL96-DMX EL96-DMX

¹ See page 2


4.6/ftW 24V DC

DRIVER


CVDMX Power supply options (remote only)

EL96-DMX

Dry location 96W 24V
RGBW Sequencer, DMX
dimnable



Profile



E99549 Anod. Al.

E-K100007 Black A.A.
Linear profile
Length 39.4 in



E83034 Anod. Al.

E-K100009 Black A.A.
Linear profile with
cable run
Length 39.4 in



E-F400001 Anod. Al.

E-F400002 Black A.A.
Clip with
toothed spring
Length 2 in

E-F400003 Anod. Al.

E-F400004 Black A.A.
Clip with toothed
spring with cable run
Length 2 in

Cables



E-W200005

male connector
78.7 in


E-W200006

female connector
78.7 in




E-K100011
Flexible Profile 39.64 x
0.51 x 0.63 in

Anod. Al.




E83351
Spike with bracket
(requires linear profile
or clip ordered
separately)

PVC




E83352
Tilting bracket
(requires linear profile
or clip ordered
separately)



E-V200005
Profile drilling
template (to allow
the passage of the
cable gland)



E99539
Pair of end caps
and silicone tube



E99521
Polystyrene Concrete-pour
preparation kit for E83034
profile only (not to be used
on curved runs) 1.6"H x
0.9"W x 39.8"L