

Xenia Wall Frosted – Remote Driver



General: Xenia is a family of slim profile, low glare linear LED recessed and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The recessed version can be installed as a drive-over in-grade or can be mounted into walls and ceilings. The wall version offers several mounting brackets and anti-glare visors to direct light only where needed. Multiple optics, internal Micro-louvers and a PRO version for higher output complete the range.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (20 µm).

Trim: Frameless, ideal for continuous runs.

Mounting: Adjustable steel brackets available in different lengths.

Dimensions/Weight: 14.4" (0.99 lbs) – 24.8" (1.54 lbs) – 36.6" (2.21 lbs) – 48.4" (2.87 lbs) – 60.2" (3.53 lbs)

Driver: Remote CV, 120/277V Dimmable 0-10V or Non-Dim.

Wattages: 6.5W (14.4") – 13W (24.8") – 19.5W (36.6") – 26W (48.4") – 32.5W (60.2")

Cable: Fixture comes with 0.66' of cable (Power cable required, ordered separately).

Safety features: Built-in TCS® (Moisture protection), Over tension and Electrical discharge protection systems.

IP rating: IP66. Fixture is protected against dust and direct exposure to powerful water jets.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed, Frosted. Anti-glare visors available as accessory.

Color temperatures: 2700K – 3000K – 3500K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



14.4" (6.5W)
24.8" (13W)
36.6" (19.5W)
48.4" (26W)
60.2" (32.5W)


Delivered Lumens*	14.4"	24.8"	36.6"	48.4"	60.2"
GE	163	326	459	612	765

*Values shown for 3000K

Ordering Information											
Product	Mounting/Frame	Type	Length	Wattage/Operation	Color Temp	Optic	+	Driver (Required) ¹	Cables ¹	Fixing Brackets ¹	Anti-glaring ¹
XE = Xenia	W = Wall	FR = Frosted	14 = 14.4"	7 CV = 6.5W / Remote Constant Voltage 24V DC Driver	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	GE = General illumination	+	OT96-D010 OT96-JBX	E99216 E89190 E98437 E98149 E89188	E98949 E89045 E89046 E89047	E98782 (14) E98783 (25) E98784 (37) E98785 (48) E99778 (60)
			25 = 24.8"	13 CV = 13W / Remote Constant Voltage 24V DC Driver							
			37 = 36.6"	20 CV = 19.5W / Remote Constant Voltage 24V DC Driver							
			48 = 48.4"	26 CV = 26W / Remote Constant Voltage 24V DC Driver							
			60 = 60.2"	33 CV = 32.5W / Remote Constant Voltage 24V DC Driver							

¹ See page 2

14.4" 6.5W CV



DRIVER OPTIONS (pick one)

Power supply options (remote only)


OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-dim, 96W, 24VDC, 120-277VAC, Wet location

24.8" 13W CV



DRIVER OPTIONS (pick one)

Power supply options (remote only)


OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-dim, 24VDC, 120-277VAC, Wet location

36.6" 19.5W CV



DRIVER OPTIONS (pick one)

Power supply options (remote only)


OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-dim, 24VDC, 120-277VAC, Wet location

48.8" 26W CV



DRIVER OPTIONS (pick one)

Power supply options (remote only)


OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-dim, 24VDC, 120-277VAC, Wet location

60.2" 32.5W CV



DRIVER OPTIONS (pick one)

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-dim, 24VDC, 120-277VAC, Wet location

Cables

E99216	E89190	E98437	E98149	E89188
59" low volt. power feed cable F 4 pin M12	196" low volt. power feed cable F 4 pin M12	39" low volt. power extension cable M+F 4 pin M12	196.9" low volt. power extension cable M+F 4 pin M12	393.7" low volt. power extension cable M+F 4 pin M12

Accessories

Steel fixing brackets	Anti-glaring accessory
1.8-2.6" E98949	14.4" E98782
3.5" E89045	24.8" E98783
5.9" E89046	36.6" E98784
11.8" E89047	48.4" E98785
	60.2" E99778

