



Luminaire

- IP66 rated LED marker pole with carbon fibre wand, diffuser and ground spike.
- Exterior rated decorative marker light. Ideal for subtle vegetation illumination, way finding or use in large scale dynamic scenery schemes.
- Housing Precision machined from 70 - 90% recycled aluminum.
- Mounting ground spike.
- Precision machined from 70 - 90% recycled aluminum.
- Optics Frosted diffuser for soft glow effect, Clear diffuser for 'twinkle' effect.
- LED 95+ CRI, multiple CCTs available.
- 5 Year warranty.

Height

- 12 = 11.8" (300mm)
- 20 = 19.7" (500mm)
- 30 = 29.5" (750mm)
- 40 = 39.4" (1000mm)

Mounting

- GS = Ground Spike

Power¹

- L = Low Power, 1.4W (137lm initial at 500mA, 2.85Vf)

CCT (95+ CRI)²

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Beam

- DF = Diffused
- CL = Clear

Finish

- CA = Clear anodized
- BL = Matte black
- CF = Custom finish, specify RAL

Remote Driver³

- ECO30W-500 = 0-10V EldoLED ECOdrive 30W for 1-10 fixtures
- SOLO50W-500 = 0-10V EldoLED SOLOdrive 50W for 1-20 fixtures
- SOLO100W-500 = 0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

1. Wattage shown is for LED only, system wattage varies depending on driver selected.
2. See photometric data sheet for delivered lumens.
3. See driver information for details.

Ordering Information

Model	Height	Mounting	Power ¹	CRI/ CCT ²	Beam	Finish	+	Driver ³
MS-FIR		GS	L					
MS-FIR	12 20 30 40	GS	L	927 930 935 940	DF CL	CA BL CF		ECO30W-500 SOLO50W-500 SOLO100W-500