


Loro Adjustable

ROUND ADJUSTABLE


LOR-RWH-A-...-SP...			
Delivered Lumens - Spot			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	1122	2097
	92-30-	1199	2254
	92-35-	1199	2254
	92-40-	1290	2413
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.53	1.00



Beam Angle (0-180) = 15.4
Beam Angle (90-270) = 15.6

CONE OF LIGHT - 25W 3000K Spot LOR-RWH-A-55-25-CC-92-30-SP*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	4089	0.5
4	1022	1.1
6	454	1.6
8	256	2.2
10	164	2.7
12	114	3.2
14	83	3.8
16	64	4.3
18	50	4.9
20	41	5.4


LOR-RWH-A-...-FL...			
Delivered Lumens - Flood			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	1183	1986
	92-30-	1266	2135
	92-35-	1266	2135
	92-40-	1361	2284
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.59	1.00



Beam Angle (0-180) = 33.8
Beam Angle (90-270) = 33.6

CONE OF LIGHT - 25W 3000K Flood LOR-RWH-A-55-25-CC-92-30-FL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	1221	1.2
4	305	2.4
6	136	3.6
8	76	4.9
10	49	6.1
12	34	7.3
14	25	8.5
16	19	9.7
18	15	10.9
20	12	12.2

LOR-RWH-A-...-WFL...			
Delivered Lumens - Wide Flood			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	1104	2069
	92-30-	1180	2225
	92-35-	1180	2225
	92-40-	1270	2072
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.53	1.00



Beam Angle (0-180) = 56.4
Beam Angle (90-270) = 56.2


CONE OF LIGHT - 25W 3000K Wide Flood LOR-RWH-A-55-25-CC-92-30-WFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	712	2.1
4	178	4.3
6	79	6.4
8	45	8.6
10	28	10.7
12	20	12.9
14	15	15.0
16	11	17.2
18	9	19.3
20	7	21.4

*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

** Beam Diameter indicates on center spacing required to maintain Illuminance at Mounting Height.

ROUND ADJUSTABLE HONEYCOMB


LOR-RWH-AHC-...-SP...			
Delivered Lumens - Spot			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	688	1397
	92-30-	735	1502
	92-35-	735	1502
	92-40-	791	1608
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.49	1.00



Beam Angle (0-180) = 16.4
Beam Angle (90-270) = 16.2

CONE OF LIGHT - 25W 3000K Spot LOR-RWH-AHC-55-25-CC-92-30-SP*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	2718	0.6
4	679	1.2
6	302	1.7
8	170	2.3
10	109	2.9
12	75	3.5
14	55	4.0
16	42	4.6
18	34	5.2
20	27	5.8


LOR-RWH-AHC-...-FL...			
Delivered Lumens - Flood			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	782	1278
	92-30-	836	1374
	92-35-	836	1374
	92-40-	900	1470
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.61	1.00



Beam Angle (0-180) = 29.4
Beam Angle (90-270) = 29.2

CONE OF LIGHT - 25W 3000K Flood LOR-RWH-AHC-55-25-CC-92-30-FL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	979	1.0
4	245	2.1
6	109	3.1
8	61	4.2
10	39	5.2
12	27	6.3
14	20	7.3
16	15	8.4
18	12	9.4
20	10	10.5

LOR-RWH-AHC-...-WFL...			
Delivered Lumens - Wide Flood			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	650	1211
	92-30-	695	1302
	92-35-	695	1302
	92-40-	748	1394
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.53	1.00



Beam Angle (0-180) = 44.4
Beam Angle (90-270) = 44.4

CONE OF LIGHT - 25W 3000K Wide Flood LOR-RWH-AHC-55-25-CC-92-30-WFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	573	1.6
4	143	3.3
6	64	4.9
8	36	6.5
10	23	8.2
12	16	9.8
14	12	11.4
16	9	13.1
18	7	14.7
20	6	16.3


*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

** Beam Diameter indicates on center spacing required to maintain Illuminance at Mounting Height.

Loro Adjustable

SQUARE ADJUSTABLE


LOR-SWH-A-...-SP...			
Delivered Lumens - Spot			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	1122	2097
	92-30-	1199	2254
	92-35-	1199	2254
	92-40-	1290	2413
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.53	1.00



Beam Angle (0-180) = 15.4
Beam Angle (90-270) = 15.6

CONE OF LIGHT - 25W 3000K Spot LOR-SWH-A-55-25-CC-92-30-SP*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	4089	0.5
4	1022	1.1
6	454	1.6
8	256	2.2
10	164	2.7
12	114	3.2
14	83	3.8
16	64	4.3
18	50	4.9
20	41	5.4


LOR-SWH-A-...-FL...			
Delivered Lumens - Flood			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	1183	1986
	92-30-	1266	2135
	92-35-	1266	2135
	92-40-	1361	2284
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.59	1.00



Beam Angle (0-180) = 33.8
Beam Angle (90-270) = 33.6

CONE OF LIGHT - 25W 3000K Flood LOR-SWH-A-55-25-CC-92-30-FL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	1221	1.2
4	305	2.4
6	136	3.6
8	76	4.9
10	49	6.1
12	34	7.3
14	25	8.5
16	19	9.7
18	15	10.9
20	12	12.2

LOR-SWH-A-...-WFL...			
Delivered Lumens - Wide Flood			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	1104	2069
	92-30-	1180	2225
	92-35-	1180	2225
	92-40-	1270	2072
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.53	1.00



Beam Angle (0-180) = 56.4
Beam Angle (90-270) = 56.2


CONE OF LIGHT - 25W 3000K Wide Flood LOR-SWH-A-55-25-CC-92-30-WFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	712	2.1
4	178	4.3
6	79	6.4
8	45	8.6
10	28	10.7
12	20	12.9
14	15	15.0
16	11	17.2
18	9	19.3
20	7	21.4

*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

** Beam Diameter indicates on center spacing required to maintain Illuminance at Mounting Height.

SQUARE ADJUSTABLE HONEYCOMB


LOR-SWH-AHC-...-SP...			
Delivered Lumens - Spot			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	688	1397
	92-30-	735	1502
	92-35-	735	1502
	92-40-	791	1608
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.49	1.00



Beam Angle (0-180) = 16.4
Beam Angle (90-270) = 16.2

CONE OF LIGHT - 25W 3000K Spot LOR-SWH-AHC-55-25-CC-92-30-SP*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	2718	0.6
4	679	1.2
6	302	1.7
8	170	2.3
10	109	2.9
12	75	3.5
14	55	4.0
16	42	4.6
18	34	5.2
20	27	5.8


LOR-SWH-AHC-...-FL...			
Delivered Lumens - Flood			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	782	1278
	92-30-	836	1374
	92-35-	836	1374
	92-40-	900	1470
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.61	1.00



Beam Angle (0-180) = 29.4
Beam Angle (90-270) = 29.2

CONE OF LIGHT - 25W 3000K Flood LOR-SWH-AHC-55-25-CC-92-30-FL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	979	1.0
4	245	2.1
6	109	3.1
8	61	4.2
10	39	5.2
12	27	6.3
14	20	7.3
16	15	8.4
18	12	9.4
20	10	10.5

LOR-SWH-AHC-...-WFL...			
Delivered Lumens - Wide Flood			
		Diameter [Wattage]	
		39 [13 CC]	55 [25 CC]
CCT	92-27-	650	1211
	92-30-	695	1302
	92-35-	695	1302
	92-40-	748	1394
Polar Plot / Cone Of Light Multiplier			
		39 [13 CC]	55 [25 CC]
		0.53	1.00



Beam Angle (0-180) = 44.4
Beam Angle (90-270) = 44.4

CONE OF LIGHT - 25W 3000K Wide Flood LOR-SWH-AHC-55-25-CC-92-30-WFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	573	1.6
4	143	3.3
6	64	4.9
8	36	6.5
10	23	8.2
12	16	9.8
14	12	11.4
16	9	13.1
18	7	14.7
20	6	16.3

*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

** Beam Diameter indicates on center spacing required to maintain Illuminance at Mounting Height.