



Luminaire

- Interior rated, miniature and fully adjustable fitting with curved optic designed to discreetly light archways and window reveals.
- Surface mounted.
- Precision machined from 70 - 90% recycled aluminum.
- Radial beam (9° x 113°).
- 95+ CRI, multiple CCTs available.

Mounting

- SM = Surface Mounted

Power¹

- 2 = 2W (Oscon Star, 181lm initial at 700mA, 2.9Vf)

CCT (95+ CRI)²

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Beam

- R = Radial (9°x113°)

Finish

- CA = Clear Anodized
- CB = Classic Bronze 34
- W = Pure White, RAL9010
- BA = Black Anodized
- CF = Custom finish, specify RAL

Remote Driver³

- ECO30W-700 = 0-10V EldoLED ECOdrive 30W for 1-10 fixtures
- SOLO50W-700 = 0-10V EldoLED SOLOdrive 50W for 1-20 fixtures
- SOLO100W-700 = 0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

1. Wattage shown is for LED only, system wattage varies depending on driver selected.

2. See photometric data sheet for delivered lumens.

3. See driver information for details.

Ordering Information

Model	Mounting	Power ¹	CRI/CCT ²	Optic	Finish	+	Driver ³
MS-NI	SM	2		R			
MS-NI	SM	2	927 930 935 940	R	CA CB W BL CF		ECO30W-700 SOLO50W-700 SOLO100W-700

