



Luminaire

- IP66 rated miniature spot light.
- Adjustable and lockable exterior spot light for accent lighting; very discreet for enhancing architectural details enabling "layers" within landscapes.
- Surface mounted, ground spike or pole clamp.
- Precision machined from 70 - 90% recycled aluminum.
- Optics Frosted diffuser for soft glow effect, Clear diffuser for 'twinkle' effect.
- LED 95+ CRI, multiple CCTs available.
- 5 Year warranty.

Mounting

- SM = Surface mount
- GS = Ground spike
- PC = Pole clamp

Power¹

- L = Low Power, 1.4W (137lm initial at 500mA, 2.85Vf)

CCT (95+ CRI)²

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Beam

- M = Medium 28°
- W = Wide 39.1°
- WF = Wide Flood 68.9°
- A = Asymmetric 27.4° x 43.3°

Optic

- M = Medium 28°
- W = Wide 39.1°

Diffuser

- FD = Frosted diffuser
- CD = Clear diffuser

Finish

- CA = Clear anodized
- BL = Matte black
- CF = Custom finish, specify RAL

Remote Driver³

- ECO30W-500 = 0-10V EldoLED ECOdrive 30W for 1-10 fixtures
- SOLO50W-500 = 0-10V EldoLED SOLOdrive 50W for 1-20 fixtures
- SOLO100W-500 = 0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

1. Wattage shown is for LED only, system wattage varies depending on driver selected.
2. See photometric data sheet for delivered lumens.
3. See driver information for details.

Ordering Information

Model	Mounting	Power ¹	CRI/CCT ²	Beam	Optic	Diffuser	Finish	+	Driver ³
MS-PIP		L							
MS-PIP	SM GS PC	L	927 930 935 940	M W WF A	M W	FD CD	CA BL CF		ECO30W-500 SOLO50W-500 SOLO100W-500