# reed solar set

inter·lux

Solar Powered Bollards with Automatic Operation

Includes
1X reed M 49"
1X reed L 59"
1X solar panel L

reed M solar

ø0.2"
10"
49.2"
5.1"
13"
9.8"

reed L solar

ø0.2"
10"
59"
5.1"
13"
10"

reed solar set	color	item no.	system performance
59 49.2	● **deep black RAL 9005**	93820-BL	**2x 0.55 W/11 lm**

technical information:
LED
lithium-ion battery
1x 2600 mAh
2700K
solar panel S

operating time:
automatic switch-on at dusk
for a duration of approx. 5 hrs

connection:
1x reed M solar join deep black with 4.6 ft
supply cable (05RN8-F 2x0.75 mm²)
1x reed L solar join deep black with 3.9 ft
supply cable (05RN8-F 2x0.75 mm²)
1x solar panel S deep black with 3.3 ft supply
cable (05RN8-F 2x0.75 mm²)
1x port 2

movable

material:
lluminaire: aluminum die-casting powder-coated
+ smoke-colored glass;
pole: stainless steel powder-coated;
solar panel: head: aluminum die-casting
powder-coated + clear glass;
pole: stainless steel powder-coated

protection class:
IP65

A
↑ E
G

light direction:

◉

IP44.DE

410 381 1497   inter-lux.com   answers@inter-lux.com
Inter-lux reserves the right to make technical changes without notice.

Updated 5.2024   1