



**Luminaire**

- IP66 rated LED bollard with acrylic diffuser and ground spike. Exterior rated re-buildable miniature bollard with robust construction and frosted acrylic diffuser. Ideal for lighting pathways or borders.
- Ground spike mounted.
- Precision machined from 70 - 90% recycled aluminum.
- 95+ CRI with multiple CCTs available.

**Height**

- 12 = 11.8" (300mm)
- 20 = 19.7" (500mm)
- 30 = 29.5" (750mm)
- 40 = 39.4" (1000mm)

**Mounting**

- GS = Ground Spike

**Power<sup>1</sup>**

- 2 = 2W (181lm initial at 700mA, 2.9Vf)

**CCT (95+ CRI)<sup>2</sup>**

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

**Diffuser**

- FD = Frosted diffuser for soft glow effect

**Finish**

- CA = Clear Anodized
- CB = Classic Bronze 34
- BA = Black Anodized
- CF = Custom finish, specify RAL

**Remote Driver<sup>3</sup>**

- ECO30W-500 = 0-10V EldoLED ECOdrive 30W for 1 fixture
- SOLO50W-500 = 0-10V EldoLED SOLOdrive 50W for 1-2 fixtures
- SOLO100W-500 = 0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

1. Wattage shown is for LED only, system wattage varies depending on driver selected.
2. See photometric data sheet for delivered lumens.
3. See driver information for details.

Ordering Information							
Model	Height	Mounting	Power <sup>1</sup>	CRI/CCT <sup>2</sup>	Diffuser	Finish	Driver <sup>3</sup>
MS-BUL	12 20 30 40	GS	2	927 930 935 940	FD	CA CB BA CF	ECO30W-500 SOLO50W-500 SOLO100W-500

