



### Luminaire

- Interior rated spot light with zoomable lens or fixed focus optics.
- Surface, stem or pole clamp mounted.
- Precision machined from 70 - 90% recycled aluminum.
- 95+ CRI with multiple CCTs and optics available.

### Mounting

- SM = Surface Mounted
- ST6 = 6" Stem Mounted<sup>1</sup>
- ST12 = 12" Stem Mounted<sup>1</sup>
- ST19 = 19" Stem Mounted<sup>1</sup>
- STXX = Specify Cust
- PC = Pole Clamp (clamp only, contact us for custom pole options)<sup>1</sup>

### Power<sup>2</sup>

- 8 = 8W (798lm initial at 250mA, 34.1Vf)
- 12 = 12W (1513lm initial at 350mA, 36.9Vf)
- 24 = 24W (2745lm initial at 700mA, 36.7Vf)

### CCT (95+ CRI)<sup>3</sup>

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

### Optic

- VN = Very Narrow (11°), 8W Only
- N = Narrow (15°), 12W Only
- M = Medium (25°), 24W Only
- F1 = Flood 1 (32°), 24W Only
- F2 = Flood 2 (46°), 24W Only
- WF = Wide Flood (61°), 24W Only
- WW = Wall Wash (81° x 41°), 24W Only

### Finish (interior always matte black)

- W = Pure White, RAL9010
- BL = Matte Black, RAL9005
- CF = Custom finish, specify RAL

### Options<sup>4,5</sup>

- SCS = Slash Cut Snoot
- SNT = Straight Snoot
- BD = Barn Doors

### Accessories<sup>4</sup>

- CL = Clear Lens
- DL = Diffused Lens
- HCL = Honeycomb Louver
- SOL = Solite Lens
- SHS = Sharp Spread Lens
- SOS = Soft Spread Lens

### Remote Driver<sup>6</sup>

- ECO30W-XXX = 0-10V EldoLED ECOdrive 30W  
8W, 250mA, 1 fixture  
12W, 350mA, 1 fixture  
24W, 700mA, 1 fixture
- SOLO50W-XXX = 0-10V EldoLED  
SOLOdrive 50W  
8W, 250mA, 1-2 fixtures (1 per output)  
12W, 350mA, 1-2 fixtures (1 per output)  
24W, 700mA, 1 fixture (1 per output)
- SOLO100W-XXX = 0-10V EldoLED  
SOLOdrive 100W  
8W, 250mA, 1-4 fixtures (1 per output)  
12W, 350mA, 1-4 fixtures (1 per output)  
24W, 700mA, 1-3 fixtures (1 per output)

1. See page 5 for details.
2. Wattage shown is for LED only, system wattage varies depending on driver selected.
3. See photometric data sheet for delivered lumens.
4. Holds one option or accessory. See options on page 6 and accessories on page 7 for details.
5. Outside same finish as fixture, inside matte black.
6. See driver information for details.

### Ordering Information

Model	Mounting	Power <sup>2</sup>	CRI/CCT <sup>3</sup>	Optic	Finish	Options <sup>4,5</sup>	Accessories <sup>4</sup>	+	Driver <sup>6</sup>
MS-ZTA70S	SM	8	927	VN	W	SCS	CL		ECO30W-XXX
	ST6 <sup>1</sup>	12	930	N	BL	SNT	DL		SOLO50W-XXX
	ST12 <sup>1</sup>	24	935	M	CF	BD	HCL		SOLO100W-XXX
	ST19 <sup>1</sup>		940	F1			SOL		
	STXX <sup>1</sup>			F2			SHS		
	PC <sup>1</sup>			WF			SOS		
				WW					

