



Luminaire

- Interior rated spot light with interchangeable optics. Adjustable and lockable miniature surface mount luminaire for museum showcase lighting, retail, hospitality and other close work applications.
- Surface mounted.
- Precision machined from 70 - 90% recycled aluminum.
- 95+ CRI with multiple CCTs and optics available.

Mounting

- SM = Surface Mounted

Power¹

- 3 = 3W (253lm initial at 1050mA, 3Vf)

CCT (95+ CRI)²

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Optic

- VN = Very Narrow (11.8°)
- N = Narrow (14°)
- M = Medium (20.8°)
- F = Flood (29.8°)
- WF = Wide Flood (61.1°)
- E = Elliptical (11.9° x 46.8°)

Finish (interior always black)

- CA = Clear Anodized
- W = Pure White, RAL9010
- BA = Black Anodized
- CF = Custom finish, specify RAL

Remote Driver³

- ECO30W-500 = 0-10V EldoLED ECOdrive 30W for 1 fixture
- SOLO50W-500 = 0-10V EldoLED SOLOdrive 50W for 1-2 fixtures
- SOLO100W-500 = 0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

1. Wattage shown is for LED only, system wattage varies depending on driver selected.
 2. See photometric data sheet for delivered lumens.
 3. See driver information for details.

Ordering Information

Model	Mounting	Power ¹	CRI/ CCT ²	Optic	Finish	+	Driver ⁴
MS-STG	SM	3					
MS-STG	SM	3	927 930 935 940	VN N M F WF E	CA W BA CF		ECO30W-500 SOLO50W-500 SOLO100W-500

