



SKI-SSRBLO-F-...-SP...			
Delivered Lumens - Spot			
		Diameter [Wattage]	
		7 [10 CC]	9 [17 CC]
CCT	27-	513	1022
	30-	513	1022
	40-	554	1105
Polar Plot / Cone Of Light Multiplier			
		7 [10 CC]	9 [17 CC]
		0.50	1.00



Beam Angle (0-180) = 15.2°
Beam Angle (90-270) = 14.4°

CONE OF LIGHT - 16.8W 3000K Spot SKI-SSRBLO-F-9-17-CC-30-SP*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	2045	0.5
4	511	1.1
6	227	1.6
8	128	2.1
10	82	2.7
12	57	3.2
14	42	3.7
16	32	4.3
18	25	4.8
20	20	5.3


SKI-SSRBLO-F-...-FL...			
Delivered Lumens - Flood			
		Diameter [Wattage]	
		7 [10 CC]	9 [17 CC]
CCT	27-	732	1238
	30-	732	1238
	40-	789	1337
Polar Plot / Cone Of Light Multiplier			
		7 [10 CC]	9 [17 CC]
		0.59	1.00



Beam Angle (0-180) = 33.0°
Beam Angle (90-270) = 31.6°

CONE OF LIGHT - 16.8W 3000K Flood SKI-SSRBLO-F-9-17-CC-30-FL*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	939	1.2
4	235	2.4
6	104	3.6
8	59	4.7
10	38	5.9
12	26	7.1
14	19	8.3
16	15	9.5
18	12	10.7
20	9	11.8

SKI-SSRBLO-F-...-MWFL...			
Delivered Lumens - Medium Wide Flood			
		Diameter [Wattage]	
		7 [10 CC]	9 [17 CC]
CCT	27-	594	1039
	30-	594	1039
	40-	642	1122
Polar Plot / Cone Of Light Multiplier			
		7 [10 CC]	9 [17 CC]
		0.57	1.00



Beam Angle (0-180) = 47.0°
Beam Angle (90-270) = 46.4°

CONE OF LIGHT - 16.8W 3000K Medium Wide Flood SKI-SSRBLO-F-9-17-CC-30-MWFL*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
2	477	1.7
4	119	3.5
6	53	5.2
8	30	7.0
10	19	8.7
12	13	10.4
14	10	12.2
16	7	13.9
18	6	15.7
20	5	17.4

*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.